

Spray Coat – Mix



Innovative & Decorative Concrete Technology

- **PRODUCT DESCRIPTION**

Spray Coat™ is a ready to use, co-polymer modified resurfacing compound especially formulated to bond to almost any porous concrete surface. Due to its high strength and easy workability, **Spray Coat™** is perfect to repair rain damaged slabs, scaling or dusting concrete, low spots, chipped or damaged steps and curbs as well as facing foundations. **Spray Coat™** can be applied from a feather edge up to 1/2" thick. **Spray Coat™** can be broom, sprayed or trowel finished.

- **SURFACE PREPARATION**

The concrete surface must be clean and free of all loose material, oil residue and have no sealers or paints. Clean thoroughly by using a pressure washer with a degreaser. Etch the surface using 1 part Super blue Solutions to 4 parts water.

MIXING INSTRUCTIONS

In a clean 20 Ltr bucket measure 4.5 to 5 Ltrs of clean water (and add color pack at this time). Using a drill with a mixing wand, slowly add the dry **Spray Coat™** to the water as you are running the mixing wand. Once you have added all the material, continue to mix thoroughly for 2 minutes to a plastic consistency with no lumps. Smaller portions use the enough water to mix to a plastic consistency.

- **APPLICATION INSTRUCTIONS**

Patch & leveling: Start by misting the surface with water, (surface should be damp only, no standing water) and then apply the **Patch-It™** compound. Screed where necessary, smooth with a round edged Fresno or pool trowel, keeping all tools clean and moist, and finish as desired. If the area to be patched is thicker than 1", two or more applications may be necessary. Wait until the first application is dry, (1-3 hours) and then reapply.

Base Coat: Using a steel trowel or a squeegee applies an even coat of the desired color **Spray Coat™** about 1/16th of an inch thick. Allow to dry before continuing.

Spray Coat: Using a hopper gun and an air compressor set at around 20 lbs shoot the top coat of **Spray Coat™** material. Before the material sets all the way, pass a pool trowel across the surface creating flats as you go along.

Finishing: After the surface is completely dry, lightly scrape the deck with a flat floor scraper. Blow off any debris and seal. Roll or spray 2-3 coats of Hicrete's **High Gloss Sealer™**. Allow 24 hrs for foot traffic or 48 hrs for auto traffic.

Hicrete Decorative Systems Pvt. Ltd.

Aseem Bungalow, Plot No. 36, Sant Eknathnagar (Part II), Survey no. 680/2, Bibwewadi, Pune -411037, Maharashtra, INDIA Tell : 020-24211992

Spray Coat – Mix



Innovative & Decorative Concrete Technology

- **COVERAGE** Covers 75 to 80 Sq Ft. per Bag

- **PRODUCT SPECIFICATIONS**

ASTM C-109 Compressive Strength ASTM C-882 Bond Strength

1 Day 30 N/mm² 7 Day 12.35 N/mm²

7 Day 40 N/mm²

28 Day 45 N/mm²

- FOR PROFESSIONAL USE ONLY. KEEP OUT OF REACH OF CHILDREN.

Avoid contact with skin, wash exposed areas promptly. Wear eye protection. If **Spray Coat™** gets in eyes, flush with clean water and seek medical attention. Contains silica sand, do not inhale **Spray Coat™**. Wear a dust mask or suitable breathing apparatus.

LIMITED WARRANTY: This product is warranted to be of uniform quality within manufacturing tolerances. Since no control is exercised over its use, no warranty expressed or implied, is made as to the effect of such use. Seller's and Manufacturer's obligation under this warranty shall be limited to refunding the purchase price of that portion of the material proven to be defective.

HiCrete Decorative Systems Pvt. Ltd.

Aseem Bungalow, Plot No. 36, Sant Eknathnagar (Part II), Survey no. 680/2, Bibwewadi, Pune -411037, Maharashtra, INDIA Tell : 020-24211992